
D60 Hardcore Locking Hub Installation Instructions



NO.	QTY	DESCRIPTION
1	2	BEZEL
2	2	SELECTOR
3	2	RETAINER PLATE
4	2	CAM SPACER
5	2	DRIVER
6	2	COUPLER
7	2	SPRING
8	2	SPACER
9	12	10-24, 3/4" SHCS
10	12	NYLON WASHER
11	2	SELECTOR O-RING
12	2	HUB O-RING
13	2	AXLE SNAP RING
14	2	HUB SNAP RING
15	2	BUSHING
16	2	SPRING RETAINER

^{*} NOTE: BUSHINGS ARE PRESS FIT ONTO DRIVERS † YHC70004 DOES NOT INCLUDE SPRING RETAINERS

Tools Required:


- 5/32" Allen
- Flat Screwdriver
- 1/4" Allen
- 2-5/8," OD 6-lug Spindle Nut Socket
- 7/8" Lug Wrench
- 3/4" Wrench



Remove 6 Socket head cap screws 5/32" Allen









Remove (14) HubSnap Ring with flat screwdriver or pick



Remove (3) Retainer Plate




Remove (4) Cam Spacer



Remove (13) Axle Snap Ring with flat screwdriver or pick









Current View



Remove (8) Spacer



Remove 1st Axle Nut with 2-5/8" OD 6-lug spindle nut socket






Remove Lock Ring (Teeth facing outward)




















Parts in line





Remove caliper lock screw with 1/4" Allen



Remove Wedge with punch and hammer



Brake shoes. Piston side is smaller.



Remove rotor then 6 caliper bracket nuts with 3/4" Socket



Remove spindle



Axle Seal location



Chevy d60 long side length

